



### Overview








- 3 megapixel resolution
- H.264 & MJPEG dual-stream encoding
- WDR with Day/Night (ICR), 3DNR, AWB, AGC, BLC
- 2.7-12mm Auto focus motorized lens
- 3-axis positioning
- IP67, IK10, PoE
- Micro SD card slot, up to 128GB
- IR LEDs Length 30m
- Video Insight VMS License Included

### Technical Specifications

Device	
Image Sensor:	1/3" 3Megapixel progressive scan CMOS
Scanning System:	Progressive
Electronic Shutter Speed:	Auto/Manual, 1/3(4)~1/100000s
Min. Illumination:	0. 1Lux/F1.4 (Color), 0Lux/F1.4(IR on)
Wide Dynamic Range:	WDR (>50dB)
3-Axis:	Yes
Camera Features	
Max. IR LEDs Length:	30m
Day/Night:	Auto(ICR)/Color/B/W
Backlight Compensation:	BLC / HLC / DWDR
White Balance /Gain Control:	Auto/Manual
Noise Reduction:	3D
Privacy Masking:	Up to 4 areas
Lens	
Focal Length:	2.7mm~12mm F1.4 : H: 92°~28°
Focus:	Auto
Lens Type:	Motorized/Fixed Iris
Mount Type:	Board-in Type
Video	
Compression:	H.264,MJPEG,MPEG4
Resolution:	3M(2304x1296) 2MP(1920x1080) 1.3MP (1280x960) 3M& 2MP/1080P(20fps) (1.3MP/25/30fps)



## Technical Specifications

<b>Network</b>	
Ethernet:	RJ-45 (10/100Base-T)
Wi-Fi:	NO
Protocol:	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,
Compatibility:	ONVIF, CGI
<b>Interface</b>	
Memory Slot:	Micro SD slot: up to (128GB)
RS485:	N/A
Alarm:	Motion detection
<b>General</b>	
Power Supply:	DC12V, PoE (802.3af)
Power Consumption:	<8.5W
Working Environment:	-30°C~+60°C, Less than 95% RH
Ingress Protection:	IP67
Vandal Resistance:	IK10
Dimensions:	φ122mm×89mm
Weight:	0.5kg
Audio:	NO
Accessories:	<div> <div>E-A137-JB</div>  </div> <div> <div>E-B200-FM</div>  </div> <div> <div>E-B203-WM</div>  </div> <div> <div>A-Pole Mount</div>  </div> <div> <div>A-CNR</div>  </div> <div> <div>E-A152-PM</div>  </div> <div> <div>E-A152-CM</div>  </div>